



KYORITSU · CLAMP METERS · DATASHEET

Kyoritsu KEW 2200R AC Clamp Meter

Model KEW 2200R · AC Clamp Meter



Ultra-slim 1000 A AC clamp meter weighing about 120 g, with a $\phi 33$ mm teardrop jaw and AC/DC voltage, resistance and continuity functions.

Key features

- Ultra-slim, lightweight design: 20 mm thick, approx. 120 g
- $\phi 33$ mm teardrop-shaped jaw
- 1000 A AC current with 0.01 A minimum resolution
- AC V, DC V, resistance and continuity buzzer functions
- Fuseless electronic protection on Ω / continuity up to 600 V
- IEC 61010-1 CAT IV 300 V / CAT III 600 V (AC A), IEC 61010-2-032

Price and availability

Ask Industrial Supply Syndicate for the current price, stock and a quotation with GST and freight. Call +91 8961089611 or WhatsApp +91 89610 89611.

Specifications

AC Current

Ranges and accuracy 40.00 / 400.0 / 1000 A (auto-ranging); $\pm 1.5\%$ rdg ± 5 dgt (45–65 Hz), $\pm 2.0\%$ rdg ± 5 dgt (40 Hz–1 kHz)

Conductor size $\phi 33$ mm max.

AC Voltage

Ranges and accuracy 4.000 / 40.00 / 400.0 / 600 V (auto-ranging); $\pm 1.8\%$ rdg ± 7 dgt (45–65 Hz), $\pm 2.3\%$ rdg ± 8 dgt (65–500 Hz)

DC Voltage

Ranges and accuracy 400.0 mV / 4.000 / 40.00 / 400.0 / 600 V (auto-ranging); $\pm 1.0\%$ rdg ± 3 dgt (400 mV range excluded)

Resistance & Continuity

Resistance 400.0 Ω / 4.000 / 40.00 / 400.0 k Ω / 4.000 / 40.00 M Ω (auto-ranging); $\pm 2.0\%$ rdg ± 4 dgt (0–400 k Ω), $\pm 4.0\%$ rdg ± 4 dgt (4 M Ω), $\pm 8.0\%$ rdg ± 4 dgt (40 M Ω)

Continuity buzzer Buzzer sounds below 50 ± 30 Ω

Safety

Measurement category IEC 61010-1 CAT IV 300 V / CAT III 600 V, pollution degree 2 (AC A); CAT III 300 V / CAT II 600 V, pollution degree 2 (AC/DC V)

Standards IEC 61010-031, IEC 61010-2-032, IEC 61326 (EMC), EN 50581 (RoHS)

General

Power source R03 / LR03 (AAA) (1.5 V) $\times 2$; approx. 120 hours continuous; auto power off approx. 10 minutes



General (continued)

Dimensions	190 (L) × 68 (W) × 20 (D) mm
Weight	Approx. 120 g (including batteries)

What's in the box

- Test leads (7107A)
- Carrying case (9160)
- Battery (AAA) (R03) × 2
- Instruction manual

Typical applications

- **Field Electrical Testing** – Slim 120 g clamp meter with test leads for site visits.
- **Electrical Maintenance** – AC current to 1000 A plus AC/DC voltage, resistance and continuity checks.

Official Kyoritsu documents

[KEW 2200R product catalogue \(English\)](#) PDF · www.kew-ltd.co.jp

[KEW 2200R instruction manual \(English\)](#) PDF · www.kew-ltd.co.jp

Order or ask for a quotation

Industrial Supply Syndicate supplies the Kyoritsu KEW 2200R across India with a GST invoice. Tell us the quantity and delivery location; we reply with a quotation or proforma invoice including freight.

Phone +91 8961089611
WhatsApp +91 89610 89611
Email info@kyoritsumeters.in
Online kyoritsumeters.in/product/kyoritsu-kew-2200r-ac-clamp-meter/
Address 54, Ezra Street, Kolkata, West Bengal 700000, India
GSTIN 19ACDPC1843J1ZR



Scan to WhatsApp us