



KYORITSU · INSULATION TESTERS · DATASHEET

Kyoritsu KEW 3551 Digital Insulation / Continuity Tester

Model KEW 3551 · Digital Insulation / Continuity Tester



Compact digital insulation and continuity tester with six test voltages from 50 V to 1000 V, ranges up to 4000 M Ω and a 0.5 s measurement speed.

Key features

- Six insulation test voltages: 50 / 100 / 125 / 250 / 500 / 1000 V
- Measurement speed of 0.5 s (KEW figure)
- Auto-ranging resistance / continuity 40.00 / 400.0 / 4000 Ω with 200 mA or more test current
- AC and DC voltage measurement up to 600 V
- Automatic discharge of stored charge after insulation measurement
- Backlight, auto power-off and test lead with remote control switch
- IEC 61010 CAT III 600 V / CAT IV 300 V, IEC 60529 IP40

Price and availability

Ask Industrial Supply Syndicate for the current price, stock and a quotation with GST and freight. Call +91 8961089611 or WhatsApp +91 89610 89611.

Specifications

Insulation Resistance

Test voltage	50 / 100 / 125 / 250 / 500 / 1000 V
Measuring range	100.0 M Ω (50 V), 200.0 M Ω (100 V), 250.0 M Ω (125 V), 500.0 M Ω (250 V), 2000 M Ω (500 V), 4000 M Ω (1000 V)
Mid-scale value	2 M Ω (50 V), 5 M Ω (100 V), 5 M Ω (125 V), 10 M Ω (250 V), 100 M Ω (500 V), 200 M Ω (1000 V)
First effective measuring range	0.100 to 10.00 M Ω (50 V), 0.100 to 20.00 M Ω (100 V), 0.100 to 25.00 M Ω (125 V), 0.100 to 50.0 M Ω (250 V), 0.100 to 500 M Ω (500 V), 0.100 to 1000 M Ω (1000 V)
Accuracy (first range)	$\pm 2\%$ rdg ± 2 dgt
Second effective measuring range	0.050 to 0.099 M Ω and 10.01 to 100.0 M Ω (50 V), 20.01 to 200.0 M Ω (100 V), 25.01 to 250.0 M Ω (125 V), 50.1 to 500 M Ω (250 V), 501 to 2000 M Ω (500 V), 1001 to 4000 M Ω (1000 V)
Accuracy (second range)	$\pm 5\%$ rdg (0.050 to 0.099 M Ω : $\pm 2\%$ rdg ± 4 dgt)
Rated current	1.0 to 1.1 mA
Output short circuit current	1.5 mA max

Resistance & Continuity

Ranges (auto-ranging)	40.00 / 400.0 / 4000 Ω
Accuracy	$\pm 2.5\%$ rdg ± 8 dgt
Output voltage on open circuit	5 V (4 to 6.9 V)



Resistance & Continuity (continued)

Output short circuit current 200 mA or more

Voltage

Voltage range AC 2.0 to 600 V (45 to 65 Hz); DC -2.0 to -600 V / +2.0 to +600 V

Accuracy $\pm 1\%$ rdg ± 4 dgt

Safety

Measurement category IEC 61010 CAT III 600 V / CAT IV 300 V

Standards IEC 61010-2-034, IEC 61557-1, 2, 4, IEC 61326-1, 2-2, IEC 60529 (IP40)

General

Power source LR6/R6 (AA) (1.5 V) $\times$ 4

Dimensions 97 (L) $\times$ 156 (W) $\times$ 46 (D) mm

Weight Approx. 490 g (including battery)

What's in the box

- Test lead with remote control switch (7260)
- Test lead with alligator clip (7261A)
- Extension prod long (8017A)
- Carrying case (9173)
- Shoulder strap (9121)
- Battery (LR6 (AA)) $\times$ 4
- Instruction manual

Typical applications

- **Insulation Testing** – Six test voltages from 50 V to 1000 V with ranges up to 4000 M Ω .
- **Electrical Maintenance** – Continuity, AC/DC voltage and insulation tests in one CAT IV 300 V rated tester.
- **Field Electrical Testing** – Approx. 490 g, AA powered, with remote-switch test lead.

Official Kyoritsu documents

[KEW 3551 product catalogue \(English\)](#) PDF · www.kew-ltd.co.jp

[KEW 3551 instruction manual \(English\)](#) PDF · www.kew-ltd.co.jp

Order or ask for a quotation

Industrial Supply Syndicate supplies the Kyoritsu KEW 3551 across India with a GST invoice. Tell us the quantity and delivery location; we reply with a quotation or proforma invoice including freight.

Phone +91 8961089611
WhatsApp +91 89610 89611
Email info@kyoritsumeters.in
Online kyoritsumeters.in/product/kyoritsu-kew-3551-insulation-tester/
Address 54, Ezra Street, Kolkata, West Bengal 700000, India
GSTIN 19ACDPC1843J1ZR



Scan to WhatsApp us