



KYORITSU · CLAMP METERS · DATASHEET

Kyoritsu MODEL 2433R Leakage Clamp Meter

MODEL 2433R · Leakage Clamp Meter



Leakage clamp meter covering 40 / 400 mA and 400 A AC with 0.01 mA resolution, a 40 mm jaw and a frequency selector switch to reject harmonics.

Key features

- Ranges: 40 / 400 mA / 400 A AC
- Minimum resolution 0.01 mA
- Frequency selector switch to eliminate the effect of harmonics
- Ø40 mm jaw
- Response time approx. 2 seconds
- IEC 61010-1 CAT III 300 V

Price and availability

Ask Industrial Supply Syndicate for the current price, stock and a quotation with GST and freight. Call +91 8961089611 or WhatsApp +91 89610 89611.

Specifications

AC Current

AC A (50/60 Hz)	40 / 400 mA / 400 A; $\pm 1\%$ rdg ± 5 dgt (40 / 400 mA), $\pm 1\%$ rdg ± 5 dgt (0 to 300 A), $\pm 2\%$ rdg (300.1 to 399.9 A)
AC A (WIDE)	40 / 400 mA / 400 A; $\pm 2.5\%$ rdg ± 10 dgt [20 Hz to 1 kHz] (40 / 400 mA), $\pm 2.5\%$ rdg ± 10 dgt [40 Hz to 1 kHz] (0 to 300 A), $\pm 5\%$ rdg [40 Hz to 1 kHz] (300.1 to 399.9 A)
Frequency response	20 Hz to 1 kHz (40 Hz to 1 kHz on 400 A)
Effect of external stray magnetic field	Approx. 10 mA AC in proximity to a 15 mm conductor carrying 100 A AC
Response time	Approx. 2 seconds
Maximum circuit voltage	600 V AC/DC (between line/neutral), 300 V AC/DC (against earth)
Conductor size	Ø40 mm max.

Safety

Measurement category	IEC 61010-1 CAT III 300 V, pollution degree 2
Standards	IEC 61010-2-032

General

Power source	R03 (1.5 V) $\times$ 2
Dimensions	185 (L) $\times$ 81 (W) $\times$ 40 (D) mm
Weight	Approx. 270 g (including battery)



What's in the box

- Carrying case (9097)
- Battery (AAA) (R03) × 2
- Instruction manual

Typical applications

- **Electrical Safety Testing** – Measures earth leakage with 0.01 mA resolution on live circuits.
- **RCD Testing** – Finds standing leakage responsible for RCD nuisance tripping.
- **Electrical Maintenance** – Doubles as a 400 A AC load current clamp.

Official Kyoritsu documents

[Kyoritsu Shortform Catalogue 2026 \(English\) – includes the MODEL 2433R](#) PDF · www.kew-ltd.co.jp

[MODEL 2433R instruction manual \(English\)](#) PDF · www.kew-ltd.co.jp

Order or ask for a quotation

Industrial Supply Syndicate supplies the Kyoritsu MODEL 2433R across India with a GST invoice. Tell us the quantity and delivery location; we reply with a quotation or proforma invoice including freight.

Phone +91 8961089611
WhatsApp +91 89610 89611
Email info@kyoritsumeters.in
Online kyoritsumeters.in/product/kyoritsu-model-2433r-leakage-clamp-meter/
Address 54. Ezra Street, Kolkata, West Bengal 700000, India
GSTIN 19ACDPC1843J1ZR



Scan to WhatsApp us